

The Air-Powered GO-A8-PW Pivot Wheel Gate Opener

- **SELF-REGULATING, NO REACTION TORQUE OUTPUT OF 1,000 TO 13,000 FT-LBS** — to open even the most jammed gate in < 8.2 seconds with absolutely no torque reaction to endanger the operator.
- **BAKED-ON, POWDER COAT FINISH** — to prevent rust and corrosion caused by weather conditions and the harsh environment of unloading sites.
- **ENGINEERED AND FABRICATED FOR RUGGED USE** — to insure long, dependable service. The heavy-duty steel frame uses laser cut members, welded by AWS certified welders to meet AWS and ANSI Standards.
- **PRECISE WEIGHT DISTRIBUTION** — to provide excellent balance and control, and thereby minimize operator fatigue and maximize gate opening safety.
- **AIR POWERED, PIN LOCK PIVOT WHEELS THAT ROTATE SMOOTHLY INTO POSITION** — to insure operator safety while maneuvering the opener, or when operating on either fixed or traveling gate mechanisms.
- **HEAVY DUTY PIVOT/STEERING MECHANISM WITH STEEL GUARD PROTECTION, AND EASY TO ACCESS GREASE FITTINGS** — to provide long, trouble-free operation, and fast, easy routine maintenance.



Ergonomically positioned, self-closing, speed control throttle, and positive on/off pivot wheel switch and forward/reverse lever arm

Auto-Lubricator to reduce maintenance tasks while guaranteeing critical wear components are receiving needed lubrication.

Lock Pin for secure pivot / non-pivot control

Oil Caddy with 1-Qt TOOL LUBE™ Air Motor Oil alongside Tool and Accessory Storage Container

Height Adjustable Forks: 10.5"; 12.5"; 14.5"

Capstan Drive Fitting: precision machined, 1-piece construction with 1-1/2" sq socket

Air Powered Pivot Wheels with oversized, flat-free polyurethane tires.

- **AIR-POWERED DRIVER MOTOR AND CONTROLS** — to eliminate explosion, fire and electrical shock hazards; provide instant START/STOP operation; eliminate hydraulic problems, eg, return line heat build-up that ruptures hoses and sprays high temp hydraulic fluid that burns workers or contaminates product.
- **OPERATOR TRAINING VIDEO AND THOROUGH, EASY-TO-READ, OWNER/OPERATOR MANUAL** — to provide explicit, easy-to-grasp instructions for quick training of both the operators, and the mechanics who service and maintain the opener.

WORKMASTER GATE OPENER SPECIFICATIONS

Model:	GO-A8-PW Pivot Wheel Gate Opener
Power:	Pneumatic; Requires 148 CFM @ 85 PSI (free); 114 CFM @ 85 PSI (impacting)
Working Torque:	1,000 to 13,000 ft.-lbs; recoilless, self-regulating
Wheel Assembly:	16" Dia. with 4.80 / 4.00 – 8" , flat-free, solid polyurethane tires, ribbed tread
Frame Dimensions:	41" L x 42" W x 42" H
Handle Width:	28" W; fitted with handle grips
Height Adjustment:	Height Adjustable Forks: 10.5", 12.5", 14.5" from ground to Capstan Drive Fitting
Tool Container:	5" L x 12" W x 6" D
Lubricator Capacity:	16.0 oz
Inlet Coupling:	Universal Coupling (Chicago Type) with safety lock pin
Finish Coating:	Baked-on, powder coat finish
Included Accessories:	(1) Drive Fitting with Pin & Ring Retainer; (1) Qt Air Tool Oil; (1) Video; (1) Manual
Gate Opener Weight:	306 Lbs
Shipping Weight:	465 Lbs



CALL FOR A FREE VIDEO

To learn more, request our free video:
Railroad Hopper Car Unloading Solutions.

You'll not only see the **WORKMASTER** Gate Opener in action, but also hear what our customers think about it.